

## General Specification

### Function

- Measurement
- Filing (Internal): Up to 128 events
- Communication: LAN Port

### Electrocardiograph

- Leads: Standard 12 leads
- Sensitivity:  
1/4, 1/2, 1, 2 cm/mV or automatic
- Polarization Voltage:  
 $\pm 550\text{mV}$  or greater
- Frequency Response:  
0.05 to 150Hz
- Time Constant: 3.2 sec
- Common Mode Rejection:  
2mmp-p or lower (103dB or more)
- Input Impedance:  
50M ohms or greater
- Input Circuit Current:  
 $5 \times 10^{-8}\text{A}$  or lower
- Internal Noise:  
 $20 \mu \text{Vp-p}$  or lower
- Calibrated Voltage:  
 $1\text{mV} \pm 2\%$  or lower
- Sampling rate: 1000/sec/ch
- Hum Filter: -20dB or less at 50/60Hz
- Muscle Filter:  
-3dB (-6dB/oct) at 25/35Hz
- Drift Filter: -3dB or less at 0.25/0.5Hz

### Recorder

- Recording System:  
Thermal Array Head
- Width of paper:  
50mm or 63mm (50mm: Option)
- Recording Speed:  
5, 10, 12.5, 25, 50mm/sec
- Resolution ; Deflection axis:  
8 dots/mm
- Resolution ; Time axis: 1m sec
- Recording Channels:  
1ch, 1ch+rhythm lead, 3ch
- Recording Paper ; Roll Paper:  
OP-119TE (63mm x 30m)  
OP-18TE (50mm x 30m)
- Recording Paper ; Z-fold Paper:  
OP-122TE (63mm x 20m)  
OP-123TE (50mm x 20m)



---

## Display

- Type: LCD
- Resolution:  
320 dot (horizontal) x 240 dot (vertical)
- Representation Channel: 3, 6, 12
- Patient data: ID number, age, sex

## Operation

- Membrane Keys

## Measurement Operation

- Basic Measurement Value:  
Heart Rate, R-R time, P-R time,  
QRS time, QT time, Qtc,  
Electrical Axis, SV1, RV5(6)
- Heart Rate Measurement :  
20 to 300bpm
- Accuracy:  $\pm 2$ bpm

## General

- Safety Standard: IEC60601-1  
(ClassII, Type CF; Internally Powered  
Equipment, Type CF)
- Power Supply for AC:  
100 to 240 V AC ( $\pm 10\%$ ), 50/60Hz,  
Power Consumption: 70VA
- Power Supply for DC:  
Ni-MH Battery (8HP-4/3A 3700-H-318)  
Power Consumption: 40W
- DC Operation Time: 180 min
- DC Charging Time: 150 min
- Dimensions:  
260mm(W) x 200mm(D) x 64mm(H)  
10.24 x 7.87 x 2.52 inch
- Weight: Approx. 1.2kg (2.7 lbs)

## Operating Environment

- Temperature:  
+10 to + 40 degrees Celsius  
(50 to 104 degrees Fahrenheit)
- Humidity: 25 to 95% (no condensation)
- Atmospheric Pressure:  
70 to 106 kPa (700 to 1060 mbar)

## Storage Environment

- Temperature:  
-10 to + 55 degrees Celsius  
(14 to 131 degrees Fahrenheit)
- Humidity: 10 to 95% (no condensation)
- Atmospheric Pressure:  
70 to 106 kPa (700 to 1060 mbar)